

Rhodes Race Cars - Threaded Tube Adapters

TUBE OD X WALL THICKNESS	10-32	1/4-28	5/16-24	3/8-24	7/16-20	1/2-20	5/8-18	3/4-16	7/8-14	1-14	1 1/4-12
3/8 x .058	25-1101										
1/2 x .058		25-1202	25-1203								
5/8 x .058			25-1303	25-1304	25-1305						
3/4 x .058			25-1403	25-1404	25-1405						
3/4 x .065			25-1503	25-1504	25-1505						
7/8 x .058				25-1604	25-1605	25-1606					
7/8 x .065				25-1704	25-1705	25-1706					
7/8 x .083				25-1804	25-1805	25-1806					
1 x .058				25-1904	25-1905	25-1906	25-1907				
1 x .065				25-2004	25-2005	25-2006	25-2007				
1 x .083				25-2104	25-2105	25-2106	25-2107				
1 x .095				25-2204	25-2205	25-2206	25-2207				
1 1/8 x .058						25-2306	25-2307				
1 1/8 x .065						25-2406	25-2407				
1 1/8 x .083						25-2506	25-2507	25-2508			
1 1/8 x .095						25-2606	25-2607	25-2608			
1 1/4 x .065							25-2610				
1 1/4 x .095							25-2707	25-2708			
1 1/4 x .120							25-2807	25-2808			
1 3/8 x .095							25-2907	25-2908			
1 3/8 x .120							25-3007	25-3008			
1 1/2 x .095							25-3057	25-3058			
1 1/2 x .120								25-3108	25-3109		
1 1/2 x .250								25-3208	25-3209		
1 5/8 x .083						25-3210	25-3211	25-3212			
1 3/4 x .120								25-3308	25-3309	25-3310	25-3311
1 3/4 x .250								25-3408	25-3409	25-3410	
2 x .250											25-3511

- ALL part numbers above are also available with Left Hand Thread. For ordering, add "L" at the end of part number.
- Part numbers 25-1404L & 25-2708L are also available with hex end. Add "-H" to end of part number.
Example: 25-2708L-H
- Left handed threaded parts have a distinctive mark around the outside diameter.
- Tube Ends must be welded in place by a skilled welder, using good welding techniques.